

# ZK – iFace302

## Multi-Bio Product



**ZKSoftware**  
The Advanced Biometric Solution

**AVI INFOSYS LLC**  
AUTHORISED ZKSOFTWARE  
MASTER DISTRIBUTOR



### Product Introduction

iFace 302 multi-biometric identification time attendance product adopts ZKSoftware latest ZEM600 platform with ZK Face 5.0 algorithm and large capacity memory. iFace series integrated 630MHz high speed ZK Multi-Bio processor and high definition infrared camera which enables user identification in the dark environment. The appearances of iFace series are designed by Germany professional design company according to the view of human engineering. All operations of iFace device are designed to be finished on the 4.3 inches TFT touch screen. Multi-model communications includes RS232/485, TCP/IP, optional WiFi or GPRS. Optional built-in 2000 mAh battery eliminates the trouble of power-cut.

### Quick Facts

- Integration of Fingerprint, Facial, RFID, and Password identification methods.
- Elegant design according to the view of human engineering
- 4.3" TFT touch screen, easy operation, fashionable and simple interface.
- 6 user-defined function keys
- Simple access control function reduces extra door control equipments cost for users.
- Web server management software via IE browser.
- Extendable scheduled-bell.
- Infrared optical system enables user identification in dark environment.
- Optional built-in backup battery support extra 4 hours continuous operation if power cut.
- Optional built-in wireless WiFi or GPRS communication makes easier device installation without wiring.

## Technical Specification

<b>Processor</b>	:	Multi-Bio 600
<b>Memory</b>	:	256M flash, 64 SDRAM
<b>Camera</b>	:	High Definition Infrared Camera
<b>Display</b>	:	4.3" TFT with touch screen
<b>Storage Capacity</b>		
<b>Face</b>	:	700
<b>Fingerprint</b>	:	5000
<b>Logs</b>	:	100,000
<b>Back-up Battery</b>	:	2000 mAh
<b>Communication</b>	:	TCP/IP, RS232/485
<b>USB-HOST</b>	:	Two
<b>T&amp;A functions</b>	:	Extendable Scheduled-bell, DLST, Self-Inquiry, Work Code, Short Message, T9 input Webserver
<b>Simple A&amp;C function</b>	:	electric lock, door sensor, exit button, Wiegand output
<b>Optional functions</b>	:	WIFI, GPRS, serial printer, Mifare/HID/iClass, backup battery
<b>Power Supply</b>	:	12V 3A
<b>Verification Speed</b>	:	≤2 sec
<b>Operating Temperature</b>	:	0°C - 45°C
<b>Operating Humidity</b>	:	20%-80%
<b>Dimension</b>	:	193.6 X 165.2 X 86 mm

---

**AVI Infosys LLC**  
UAE Toll free 800-284(AVI)  
Tel +971(4) 358 7036  
Fax +971(4) 358 7063  
info@avi-infosys.com

#1005, Executive suite,  
10th Floor The Park Place Building,  
Trade Centre-1  
Sheikh Zayed Road, Dubai,  
United Arab Emirates

---