

# Analogue Dome Indoor Camera

## CE and FC Certified Professional Series of CCTV Surveillance Products



1. PIXEL CMOS
2. SONY/SHARP Color CCD
3. Back Light Compensation(BLC)
4. Auto White Balance(AWB)
5. Lens: Board Lens 3.6mm/F2.0
6. Dimension : Ø88 x 58(H) mm



### Specifications

**AVI-VIS-2322**

Image Sensor	1/3"SONY
Horizontal Resolution	420 TV Line
Pixels	PAL:500(H)x582(V) NTSC:510(H)x492(V)
TV System	PAL/NTSC
Lens	Board Lens 3.6mm/F2.0(Optional)
Sync System	Internal
Usable Illumination	0.8Lux/F2.0
S/N Ratio	> = 48dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10° ~ +50° RH95% Max
Storage Temperature	-20° ~ +60° RH95% Max
White Balance	Auto
Power Source	DC12V 150mA
Dimension	88 x 58(H) mm
Weight	250g

### AVI INFOSYS LLC

#1005,Executive suite,10th Floor  
The Park Place Tower, Trade Centre-1  
Sheikh Zayed Road,PO BOX: 26813  
Dubai, United Arab Emirates  
Tel +971(4)358 7036, Fax : +971(4)358 7063  
Email: info@avi-infosys.com  
Web: www.avi-infosys.com

TOLL FREE 800 AVI (800-284)



**AVI INFOSYS**  
Define → Design → Deploy

### INTERNATIONAL OPERATIONS



An ISO 9001:2008 Certified  
IT Solutions Provider Company