ZK – iClock2500

Fingerprint Time Attendance with 3.5" / 8" TFT LCD





AVI INFOSYS LLC

AUTHORISED ZKSOFTWARE MASTER DISTRIBUTOR



Product Introduction

iClock2500 is an innovative biometric fingerprint reader for Time & Attendance applications, offering unparalleled performance using an advanced algorithm for reliability, precision and excellent matching speed. The iclock2500 features the fastest commercial-based fingerprint matching algorithm and ZK highperformance, high-image quality optical fingerprint sensor. The 8 inch TFT can display more information vividly, including user photo, fingerprint image quality and verification result etc. 8 function keys are the shortcuts to change the attendance status, work-code or to browse the short message, and can be defined as required. TCP/IP communication is standard and make sure the data transmission between terminal and PC can be easily done within several seconds. The camera can capture the image of the user. Backup battery can provide more than three hours power supply when power input fails down.

Quick Facts

- Color TFT screen with GUI Interface for ease of use.
- ZK Optical Sensor.
- High resolution camera
- Internal backup battery
- 1 touch a-second user recognition.
- Stores 8,000 templates and 200,000 transactions.
- Reads Fingerprint and/or PINs.
- Optional integrated proximity or smart card reader.
- Built-in Serial and Ethernet ports.
- Built-in USB port allows for manual data transfer when network isn't available
- Optional integrated Wi-Fi\ GPRS also available
- 8 user-defined function keys
- Multi Language Support
- Built in bell scheduling
- Real-time 1-touch data export 3rd party hosted & non-hosted applications
- Audio-Visual indications for acceptance and rejection of valid/invalid fingers
- SDK available for OEM customers and software developers.

Technical Specification		
Fingerprint Capacity	:	8000 templates
Transaction Capacity	:	200,000
Hardware Platform	:	ZEM600
Sensor	:	ZK Optical Sensor
Algorithm Version	:	ZK Finger v10.0
Communication	:	RS232/485, TCP/IP, USB-host
Camera	:	300,000 pixels camera
Standard Functions	:	Work code, SMS, DLST, Scheduled-bell, Self-Service Query, Automatic Status Switch, T9 input, photo-ID, ID card, Backup Battery, web-server
Optional Functions	:	Mifare/HID/iClass,9 digit user ID, Wi-Fi, GPRS, Printer, SOAP
Display	:	8 inches TFT Screen
Power Supply	:	12V DC 1.5A
Operating Temperature	:	0 C- 45 C
Operating Humidity	:	20%-80%
Dimension	:	314.5X256.5X79 mm
Weight With Package	:	3.10 kg
Language	:	English, Simplified Chinese, Traditional Chinese, other Languages

AVI Infosys LLC UAE Toll free 800-284(AVI) Tel +971(4) 358 7036 Fax +971(4) 358 7063 info@avi-infosys.com #1005, Executive suite, 10th Floor The Park Place Building, Trade Centre-1 Sheikh Zayed Road, Dubai, United Arab Emirates