

## CE and FC Certified Professional Series of CCTV Surveillance Products



1. Constant Speed Dome IR & IP Camera With Pre-position
2. IR LED:  $\varnothing$  5 X 24PCS IR working distance : 20M
3. Lens: Board Lens 6mm/F2.0
4. Support D1 Resolution Image
5. MPEG-4 Compression
6. Remote snapshot and video recording
- 7.Dimension :  $\varnothing$  131 X 96mm



**AVI-VIS-5010**

### Specifications

Image Sensor	1/3"SONY
Horizontal Resolution	420 TV Line
Pixels	PAL:500(H) X 582(V) NTSC:510(H) X 492(V)
Operate system	Windows 2000/XP, Linux
IR LED	$\varnothing$ 5 x 24PCS
IR Series Distance	20M
Lens	Board Lens 6mm/F2.0
Sync System	Internal
IR Status	Under 10 Lux By CDS
Usable Illumination	0 Lux/F2.0 (LED ON)
IR Power On	CDS Auto Control
S/N Ratio	=48dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )
Operation Temperature	-10° ~ +50° RH95% Max
Storage Temperature	-20° ~ +60° RH95% Max
White Balance	Auto
Power Source	DC12V1000mA
Dimension	$\varnothing$ 131 X 96mm
Weight	1300gm

### AVI INFOSYS LLC

#1005,Executive suite,10th Floor  
The Park Place Tower, Trade Centre-1  
Sheikh Zayed Road,PO BOX: 26813  
Dubai, United Arab Emirates  
Tel +971(4)358 7036, Fax : +971(4)358 7063  
Email: info@avi-infosys.com  
Web: www.avi-infosys.com

TOLL FREE 800 AVI (800-284)



**AVI INFOSYS**  
Define → Design → Deploy

### INTERNATIONAL OPERATIONS



An ISO 9001:2008 Certified  
IT Solutions Provider Company