



# **WORLD CLASS CCTV CAMERA SOLUTION**



**CCTV SECURITY SYSTEMS**  
MODEL NO. AVI-4C-DVR1005



# CE AND FC CERTIFIED PROFESSIONAL SERIES OF CCTV SURVEILLANCE PRODUCTS



## TECHNICAL SPECIFICATIONS

Video/Audio input	
Video compression	H.264
Analog video input	4-ch, BNC connector (1.0 Vp-p, 75 Ω); PAL / NTSC adaptive
Audio compression	G.711
Audio input	1-ch, RCA connector (2 Vp-p, 1 kΩ)
Voice talk input	1-ch, RCA (2.0 Vp-p, 1 kΩ) (Using AUDIO IN)
VGA output	1-ch, resolution: 1024 × 768 / 60 Hz
CVBS output	1-ch, BNC connector (1.0 Vp-p, 75 Ω); Resolution: PAL: 704 × 576, NTSC: 704 × 480
Audio output	1-ch, RCA connector (Linear, 1 kΩ)
Video/Audio output	
Recording resolution	4CIF / 2CIF / CIF
Frame rate	Main stream: 4CIF / 2CIF@12 fps, CIF@25 fps (P) / 30 fps (N)
Sub stream	CIF / QCIF@25 fps (P) / 30 fps (N)
Video bit rate	32 kbps ~ 2048 kbps, or user-defined (Max. 3072 kbps)
Stream type	Video/ Video & Audio
Audio bit rate	64kbps
Dual stream	Support
Synchronous playback	4-ch
Hard disk	
Type	1 SATA interface
Capacity	Up to 2TB capacity for each interface
External interface	
Network interface	1, RJ45 10M/100M adaptive Ethernet interface
Serial interface	1 RS-485 interface
USB interface	2, USB2.0
Others	
Power supply	12VDC
Consumption	≤10W (without hard disk or DVD-R/W)
Working temperature	-10℃~+55℃
Working humidity	10%~90%
Size(mm)	315 × 230 × 45 mm
Weight	≤2 kg (without hard disk or DVD-R/W)
Warranty	One year warranty
Annual Maintenance Contract	Available



**CALL TOLL FREE U.A.E.  
800-AVI ( 284 )**

P.O.Box 26813 Dubai, U.A.E  
Tel. +971 4 358 7036, Fax. +971 4 358 7063  
Email. info@avi-infosys.com  
International Operations :

**AN ISO 9001:2008  
CERTIFIED**  
IT SOLUTIONS PROVIDER COMPANY



[www.avi-infosys.com](http://www.avi-infosys.com)

follow us /avi-infosys